

Elektrische gegevens 24VAC/DC & 220-240VAC

24VAC/DC, Floating Control, 75% duty cycle

Model	Torque		Motor Power	Running Current	Running Time	Start Current
	N·m	in·lb	Watt	DC / 60 / 50 Hz Amp	DC / 60 / 50 Hz Sec / 90°	DC / 60 / 50 Hz Amp
OM-1	35	310	10	1.4 / 1.6 / 1.6	18 / 18 / 18	2.0 / 8.0 / 8.0
OM-A / AM	50	445	10	1.4 / 1.6 / 1.6	36 / 37 / 37	2.0 / 8.0 / 8.0
OM-2	90	800	40	2.8 / 3.4 / 3.4	18 / 18 / 17	10.0 / 11.0 / 12.0
OM-3	150	1330	40	2.6 / 3.1 / 3.1	27 / 26 / 26	10.0 / 11.0 / 12.0
OM-H	300	2655	60	3.7 / 5.3 / 5.3	25 / 20 / 20	14.0 / 28.0 / 28.0
OM-4	400	3540	80	7.7 / 9.4 / 9.4	21 / 20 / 20	20.0 / 30.0 / 30.0
OM-5	500	4430	80	7.4 / 8.9 / 9.0	28 / 26 / 26	20.0 / 30.0 / 30.0
OM-6	650	5755	80	9.0 / 11.1 / 11.6	37 / 37 / 39	20.0 / 30.0 / 30.0
OM-7	1000	8855	120	6.1 / 8.2 / 8.1	52 / 44 / 47	23.0 / 32.0 / 28.0
OM-8	1500	13280	120	9.0 / 11.1 / 11.6	58 / 55 / 58	20.0 / 30.0 / 31.0

220-240VAC, Floating Control, 75% duty cycle

Model	Torque		Motor Power	Running Current	Running Time	Start Current
	N·m	in·lb	Watt	60 / 50 Hz Amp	60 / 50 Hz Sec / 90°	60 / 50 Hz Amp
OM-1	35	310	10	0.4 / 0.4	15 / 15	2.0 / 2.0
OM-A / AM	50	445	10	0.4 / 0.4	28 / 28	2.0 / 2.0
OM-2	90	800	40	0.4 / 0.4	16 / 16	6.0 / 7.0
OM-3	150	1330	40	0.4 / 0.4	26 / 25	6.0 / 7.0
OM-H	300	2655	60	0.6 / 0.6	23 / 23	10.0 / 9.0
OM-4	400	3540	80	1.1 / 1.1	22 / 22	15.0 / 14.0
OM-5	500	4430	80	1.0 / 1.1	28 / 28	15.0 / 14.0
OM-6	650	5755	80	1.0 / 1.1	35 / 35	15.0 / 14.0
OM-7	1000	8855	120	1.2 / 1.2	59 / 58	10.0 / 10.0
OM-8	1500	13280	120	1.6 / 1.6	79 / 82	10.0 / 10.0