

# Assembled inserted drip lines

With Powertif or Supertif online drippers

## Application form

Please send us the following information if you want to receive a quotation; [info@powerplastics.com](mailto:info@powerplastics.com)

Project data	
Company name	
Contact person	
Project name	
Order number	
Desired delivery date	
Delivery to.. country/place	



Content	Example	Line 1	Line 2
Number of lines			
Line length [mtr]			
PE diameter	20, 25 or 32 mm		
PE colour	Black or White		
Spacing* between drippers [cm]			
Interval spacing* [cm]	10 - 44,2 - 10 - 44,2 - 10 etc		
Drip sets per line			
Length PE 5 mm micro tube [cm]	30 up to 100 cm		
Colour PE 5 mm micro tube [cm]	Black or White		
Blank before 1st dripper [cm]	100 cm		
Blank after last dripper [cm]	100 cm		
Rivulis Dripper ltr/h	1,1 - 1,6 - 2,2 - 3,1 - 3,85 ...		
Rivulis Model dripper	SOL, CON + Barb		
Rivulis Type dripper	ND, NDH or MOP		
Rivulis Working pressure installation [bar]	0,7 - 3,5 bar		
Naandanjain Dripper ltr/h	1,3 - 2,0 - 3,0 - 4,0 - 8,0 - 12		
Naandanjain model dripper	Barb, Taper		
Naandanjain Type dripper	PC or CNL		
Naandanjain Working pressure installation [bar]	0,5 - 4 bar		
Type stake	Snapeg, Barpeg or clickfit drop guide slim		
Stake colour	Black		

\*Regarding the spacing you need to take into account a tolerance of up to 1%



Snapeg- Barpeg - Clickfit drop guide

# Assembled inserted drip lines

With Powertif or Supertif online drippers

## Model dripper RIVULIS

**SOL** 90° barbed side outlet fits 3x5 mm micro tubes.

**Conic + Barb** matches 1-, 2- and 4way connectors + straight barbed outlet fits 3x5 mm micro tube.



SOL



Conic + Barb

## Type dripper

MOP (Medium Operating Pressure) <i>Standard dripper</i>	ND (No-Drain)	NDH (No-Drain High)
Opening pressure: 0,70 bar Sealing pressure: 0,20 bar Operating pressure range: 1,3-3,5 bar Flow rates: 1,1 – 1,6 – 2,2 – 3,1 – 3,85 – 5,3 – 8 lph	Openings pressure: 0,3 bar Sealing pressure: 0,15 bar Operating pressure range: 0,7 – 3,5bar Flow rates: 1,1 – 2,2 – 3,85 – 7,8 lph	Operating pressure: 0,50 bar Sealing pressure: 0,35 bar Operating pressure range: 1,2 – 3,5 bar Flow rates: 1,6 – 3,1 – 8,0 – 11,0 lph

## Model Naandanjain Click Tif HD Dripper

**Taper** matches 1-, 2- and 4way connectors.

**Barb** matches 1-, 2- and 4way connectors + straight barbed outlet fits 3x5 mm micro tube.



Taper



Barb

## Type dripper

PC (Heavy Duty Pressure-Compensating) & CNL (Compensating Non-leakage)
Opening pressure: 0,80 bar Sealing pressure: 0,20 bar Operating pressure range: 0,5-4,0 bar Flow rates: 1,3 – 2,0 – 3,0 – 4,0 – 8,0 – 12,0 lph